# LH15

## Bright LED Backlit Display with Side Walls (20ft x 7.5ft)

## B2 - 8x3 BACK

FRONT GRAPHIC SIZE: 237”W x 89”H
YELLOW SAFE ZONE: 231“W x 83”H
FINISHED SIZE: 236”W x 88”H

1x3 RETURN WALL GRAPHIC SIZE: 45.75”W x 89”H
YELLOW SAFE ZONE: 39.75”W x 83”H
FINISHED SIZE: 44.75”W x 88”H

# B1 - 1x3
# RETURN WALL
# + END CAP

# B3 - 1x3
# RETURN WALL
# + END CAP

**[LH15] - Bright LED Backlit Display**
**Bright LED Backlit Display with Side Walls (20ft x 7.5ft)**
Artwork Template - Back, Return Walls & End Caps

**B1 - 1x3**
**RETURN WALL**
**+ END CAP**

# LH15
## Bright LED Backlit Display with Side Walls (20ft x 7.5ft)
## B2 - 8x3 BACK

FRONT GRAPHIC SIZE: 237"W x 89"H
YELLOW SAFE ZONE: 231"W x 83"H
FINISHED SIZE: 236"W x 88"H

1x3 RETURN WALL GRAPHIC SIZE: 45.75"W x 89"H
YELLOW SAFE ZONE: 39.75"W x 83"H
FINISHED SIZE: 44.75"W x 88"H

**B3 - 1x3**
**RETURN WALL**
**+ END CAP**

Bleeding area
Safe Visual Line

Notes to Designers:

- All graphic files must be built at 150dp at the overall graphiclayout size.
- All graphic files must be created using CMYK mode to ensure the best color matching. If you would like a specific color matched, you MUST provide both PMS color and CMYK values or we cannot guarantee color matching.
- It is best to flatten all images and outline all text to ensure that nothing will be dropped out or changed during the file transfer.
- Graphics can be extended to the very edge but beware of the red visual line. Keep important images & text inside the red visual line. Images outside of the red visual line are subject to be trimmed off or covered by stitching.
- Remove the red visual line and help instructions upon submitting your artwork.

Preferred File Formats:
- .PDF (Vector Format or 100% Sized, Text Outlined)
- .JPG / .JPEG (100% Sized, 150dpi)

Acceptable File Formats:
- .AI or .EPS (Text Outlined, Images Embedded)
- .PSD (100% Sized, 150dpi)